

DRAINAGE	VALUE	
	OVER 50% SAND	UNDER 50% SAND
1. WATER TABLE BETWEEN 600mm & 1200mm	8	8
2. WATER TABLE BELOW 1200mm—NO SEWERS	6	6
3. WATER TABLE BELOW 1200mm—SANITARY SEWERS	4	6
4. WATER TABLE BELOW 1200mm—STORM SEWERS	3	6
5. WATER TABLE BELOW 1200mm—STORM & SAN. SEWERS	3	6

FROST—SEE FROST VALUE CHART

TRAFFIC	VALUE	MINIMUM ASPHALT	MINIMUM BASE 16mm CRUSHED GRAVEL
1. ARTERIAL STREETS			
—ROUTE LONGER THAN 1.6km	18	100mm	150mm
—ROUTE SHORTER THAN 1.6km	12	100mm	150mm
2. RESIDENTIAL STREETS			
—ROUTE LONGER THAN 0.8km	6	80mm	100mm
—ROUTE SHORTER THAN 0.8km	3	80mm	100mm

USE DESIGN CURVE IF TOTAL VALUE IS WITHIN LIMITS	A	B	C	D	E
	0-7	8-14	15-22	23-31	32-41

ADD VALUES FROM DRAINAGE, FROST AND TRAFFIC TABLES

DELETED