

Approved Deck Guard (Railing) Systems Low-Rise (Part 9) Residential

AlumaRail Guard Systems



Product Name

Product Description

AlumaRail Glass Railing (GR1)

- 36" Posts with 66" spacing **6 mm tempered glass** with 2" x 2" or 3" x 3" **Aluminum Posts**
- 42" Posts with 60" spacing **6 mm tempered glass** with 2" x 2" or 3" x 3" **Aluminum Posts**

AlumaRail Picket Railing (R1)

- 36" or 42" Posts with 75" spacing **3/4" x 3/4" aluminum pickets** with 3" x 3" **Aluminum Posts**

Limitations - General

- Post spacing noted is a maximum.
- Approved for surface mounted concrete and wood connections as per engineering.

Limitations – Glass Guards

- 3/4" x 3/4" aluminum picket between glass panel and post.

Limitations – Picket Guards

- Maximum spacing between aluminum pickets is 3 1/4" as per engineering.

Terms and Conditions

1. Refer to engineered documentation from manufacturer for more information (anchorage details will be attached with permit approval).
2. Only Professional Engineer Stamped Documents dated as per City of Kitchener's records have been approved.
3. The information provided on the "Approved Deck Guard (Railing) Systems" is subject to change without notice.