

Approved Deck Guard (Railing) Systems Low-Rise (Part 9) Residential

InvisiRail Guard Systems



Product Name

InvisiRail Glass Railing

Product Description

- 66" long **12 mm tempered glass** with **spigot mount**
- 84" long **12 mm tempered glass** with **wall mount**
- 42" Posts with 72" spacing **10 mm tempered glass** with stainless steel and aluminum **Invisipost**
- 42" Posts with 72" spacing **10 mm tempered glass** with 2.25" x 2.25" square Aluminum **Visti Post**
- 42" Posts with 72" spacing **10 mm tempered glass** with 2.5" x 2.5" square Aluminum **ALX Post**
- 42" Posts with 72" spacing **10 mm tempered glass** with 4" x 4" or 6" x 6" Pressure Treated **Wood Post**
- 42" Posts with 48" spacing **10 mm tempered glass** with 4" x 4" or 6" x 6" **Cedar Post**

Limitations - General

- Post spacing noted is a maximum.
- Spigot mount and wall mount requires stainless steel cap rail on top edge of tempered glass.
- Approved for surface mounted concrete and wood, fascia mounted wood, and wall bracket connections as per engineering.
- Wood posts connections must be per SB-7 connection details only.

Terms and Conditions

1. Refer to engineered documentation from manufacturer for more information (anchorage details will be attached with permit approval).
2. Only Professional Engineer Stamped Documents dated as per City of Kitchener's records have been approved.
3. The information provided on the "Approved Deck Guard (Railing) Systems" is subject to change without notice.