



Approved Deck Guard (Railing) Systems Low-Rise (Part 9) Residential

Regal Ideas Urban Rail Guard Systems

Regal ideas

<u>Product Name</u>	<u>Product Description</u>
Urban Rail Glass Railing	• 42" Posts with 72" spacing 6 mm tempered glass (66" wide) with 2 ¼" x 2 ¼" Aluminum Posts • 42" Posts with 72" spacing 6 mm tempered glass (7 ¼" wide) with 2 ¼" x 2 ¼" Aluminum Posts
Urban Rail Picket Railing	• 42" Posts with 96" spacing 5/8" x 5/8" aluminum pickets with 2 ¼" x 2 ¼" Aluminum Posts

Limitations - General

- Post spacing noted is a maximum.
- Approved for surface mounted concrete and wood, fascia wood, and wall bracket connections as per engineering.
- Mid-span support leg required.

Limitations – Glass Guards

- Maximum spacing between 7 ¼" Glass panels is 3 7/8" as per engineering.

Limitations – Picket Guards

- Maximum posts spacing is reduced to 72" at stairs
- Maximum spacing between aluminum pickets is 3 7/8" as per engineering.

Terms and Conditions

1. Refer to engineered documentation from manufacturer for more information (anchorage details will be attached with permit approval).
2. Only Professional Engineer Stamped Documents dated as per City of Kitchener's records have been approved.
3. The information provided on the "Approved Deck Guard (Railing) Systems" is subject to change without notice.